

# ENDODRY™

Drying & Storage System



TREIER  
endoscope  
part of the Duomed Group

Treier Endoscopie AG  
Chrüz matt 1, 6215 Beromünster  
Tel. +41 (0)41 510 07 00  
info@treier.com • [www.treier.com](http://www.treier.com)

Dry & Store



# A HIGHER STANDARD FOR ENDOSCOPE DRYING AND STORAGE

## ENSURE YOUR FLEXIBLE ENDOSCOPES REMAIN SAFE AND DRY DURING STORAGE

The Drying and Storage Cabinet continuously forces HEPA filtered air through all endoscope channels, ensuring the endoscope is dry and fluid-free.

- Continuous ventilation eliminates residual moisture that can lead to bacteria growth
- Circulation of dry, instrument-grade, filtered air through each endoscope channel and around the outer sheath ensures the endoscope is dry prior to use
- Short drying cycle improves scope turnaround time
- Storage time up to 31 days

## PROTECT FLEXIBLE ENDOSCOPES FROM DAMAGE

Cassette system eliminates free swinging of the distal tip and protects the endoscope during transport and storage.

- Transporting flexible endoscopes in cassettes reduces endoscope damage and related repairs by 25-30%
- Quick, efficient transfer from automated endoscope reprocessor to storage cabinet via cassette system

## CUSTOMIZABLE TO FIT YOUR FACILITY'S NEEDS

Space-conscious design available in various configurations to meet the requirements of any facility.

- Available in single-sided or pass-through models (front and back door) for separation of wet and dry areas
- Compatible with ADVANTAGE PLUS™ and ADVANTAGE PLUS™ Pass-Thru Reprocessor or DSD Reprocessor hook-ups to increase department efficiencies

## MAXIMIZE PATIENT SAFETY

The Drying and Storage Cabinet uses a cassette to minimize touching and potential recontamination.

- Reduced worker handling minimizes endoscope recontamination and optimizes infection control
- No disconnection and reconnection of endoscope channels to hook-up ensures proper connectivity and time savings
- SMART Light (green, blue, red) for quick cabinet status identification

## DATA MANAGEMENT ENSURES ENDOSCOPE DRYING CYCLE COMPLIANCE

Continuous data monitoring provides detailed information on the drying status of all endoscopes.

- Constant air circulation controls temperature and humidity within the cabinet
- Barcode scanner for ease of endoscope ID and endoscope tray location; touchscreen for quick visualization
- SMART Connect data interface with ADVANTAGE PLUS™ or ADVANTAGE PLUS™ Pass-Thru Reprocessor and CANEXIS™ Integrated Workflow Solution Tracking System



## THE COMPLETE CIRCLE OF PROTECTION

As the global vanguard in infection prevention, **only Cantel Medical delivers the Complete Circle of Protection**, a full-value, proactive partnership dedicated to helping you remove risk, streamline operational efficiencies and optimize your success.

**DRY & STORE** Bacterial growth poses significant risk to endoscopes during storage. Our Transport, Drying and Storage solutions are designed to protect valuable inventory, reduce cross-contamination touch points, eliminate moisture in the endoscope channels and control humidity. Higher humidity or moisture in endoscope channels is known to aid bacterial growth.

# DRYING AND STORAGE SYSTEM

Color touch screen display for quick identification of endoscope storage time



SMART Connect to ADVANTAGE PLUS™ or ADVANTAGE PLUS™ Pass-Thru Reprocessor and CANEXIS™ Workflow Management Software



Barcode scanner for ease of endoscope and operator identification



Compatible with ADVANTAGE PLUS™ and ADVANTAGE PLUS™ Pass-Thru Reprocessor or DSD Reprocessor hook-ups to increase efficiencies in your department

Locking doors protect endoscope inventory



Convenient transport cassette for endoscope protection and recontamination prevention

Available in left or right door swing configurations

Pass-thru and single-sided models available





### ENDODRY™ CABINET SPECIFICATIONS

#### Electrical Requirements

100-240 VAC, 50/60HZ, Power Input: 75W,  
Fuse: T2A (internal device) 15A (circuit)

#### Electrical Safety Certifications

IEC 61010-1:2010

#### Operating Temperature

10-40 °C (50-104 °F)

#### Interface

RJ45 (10/100 Mbit)

#### Dimensions

75 H x 24 W x 22 D (inches)  
190 H x 60 W x 54 D cm  
Door Swings 52 cm (20.5 inches)

#### Weight

170 kg (375 lbs)

#### Endoscope Traceability

CANEXIS™ Workflow Management Software

#### Air Requirements

(Refer to technical documents)  
Instrument grade air

### ENDODRY™ CABINET ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
15122, 15123, 15124, 15125**	ADVANTAGE PLUS™ AER - Pass-thru-model
15120, 15121*	ADVANTAGE PLUS™ AER - Single side entry model
CAS-1000	Endoscope Transport Cassette
14558	Metal Endoscope Cassette

\*\* Available in right or left door swing configurations

\*Hook-ups sold separately.

ADVANTAGE PLUS™ and ENDODRY™ are trademarks of Medivators Inc.

CANEXIS™ is a trademark of Cantel Medical Corp.

© 2017-2021 Cantel. All Rights Reserved. The Complete Circle of Protection diagram is a trademark owned by Cantel Medical Corp. and is subject to copyright protection owned by Cantel Medical Corp.

[www.cantelmedical.eu](http://www.cantelmedical.eu)

Medivators BV | t: +31 (0)45 547 1471 | e: [csdistributors@medivators.com](mailto:csdistributors@medivators.com)

© 2021 Cantel Medical Corp. LIT-00084/C-ENEU

